



## *Extend your Lifestyle®* Olympus Awning®

### *create the outdoor room*

The Olympus is a compact, fully enclosed cassette folding arm awning being only 120mm high and 204mm deep when retracted. This contemporary elliptical design is ideal for residential applications such as a small terrace courtyard or apartment block balcony.

The Olympus can be customised to sizes up to 5 metres wide and 3 metres in projection and is available as a wall mount or ceiling mount installation using extruded aluminium end fixing plates.

The Olympus awning is available in a selection of over 140 Dulux Powdercoat finishes and a large range of fabrics. The fabric is fully protected by the enclosed cassette when retracted, giving optimal protection for the fabric and operating mechanism against dirt, rain and humidity.

The Olympus can be operated manually by a crank handle and gear operation, or can be motorised with optional sun, wind and timer systems.

Aluxor Awnings is a leading manufacturer of German precision-engineered awnings, operating in Australia for over 20 years. Our awnings are built to last.





**All operating components** are designed and manufactured in Germany and certified by international testing agency TÜV to the European standard 'CE Marking'.

**The Secuflex 50 folding arms** use tensioned, spring loaded, PVC coated twin steel cables that provide added protection against corrosion. These cables are individually hung to provide excellent wind stability and fabric tension.

**The Secuflex 50 twin cable arms are able to withstand** 120,000 cycles of stress, as certified by Materials Testing Authority of Germany.

**Patented pivot ball** front bar connector provides the best possible operational safety.

**Extruded aluminium profiles** provide solid, stable and long lasting quality that will not rust or vibrate in harsh conditions.

**Construction hardware** is made of marine grade 316 stainless steel.

**The fully enclosed cassette** provides optimal protection for the fabric and operating mechanism when retracted.

**Patented aluminium brackets and components** with pre-treated baked enamel finish.



## Specifications




<i>Dimensions (h x d)</i>	✓ 120mm x 204mm
<i>Width single unit</i>	✓ 2m – 5m
<i>Projection range</i>	✓ 1.5m - 3m
<i>Inclination range</i>	✓ 5° - 35°
<i>Extruded aluminum cassette</i>	✓ 140 powdercoat colours
<i>Fabric</i>	✓ Acrylic canvas
<i>Fabric</i>	A PVC plastisol coated
<i>Operating mechanism</i>	✓ Manual
<i>Automation features</i>	A Motorised, sun, wind & timer systems
<i>Mounting brackets</i>	✓ End fixings only


✓: Standard A: Available

\*Designs and specifications for all awnings subject to change without notice.

### Wall Installation



### Ceiling Installation



Your Authorised Distributor is:

**ALUXOR** |||||  
AWNING SYSTEMS

Aluxor Awning Systems  
Aluxor Industries Pty Ltd  
[www.aluxor.com.au](http://www.aluxor.com.au)



conditions apply