

create the outdoor room

The Toga's contemporary, design makes it ideal for homes. The semi-enclosed extruded aluminium cassette protects the mechanism and fabric against dirt and corrosion. The Toga reaches sizes up to 7 metres wide and 4 metres in projection. It is available as a wall or top mount installation. Aluxor also supply customised brackets to suit site specific installations.

The Toga can be adapted to incorporate our special **Oversquare** design whereby the awning can project to a distance that is greater than its width.

A **Vario Volant** option is also available whereby a retractable vertical fabric screen, predominately see-through mesh fabric, is fitted inside the front rail. This is especially ideal for blocking out sun glare from west facing locations and seasonal low direct sun while still retaining views.

The Toga frame and extruded aluminium fascia are available in white, silver, cream, black, beige and dark grey as standard. A range of 140 colours is also available to customise the frame and fascia.

The Toga can be operated manually by a crank handle and gear operation, or can be motorised with optional sun, wind and timer systems.

Aluxor Awnings is a leading manufacturer of German precision-engineered awnings, operating in Australia for over 20 years. Using high grade materials of uncompromising quality, Aluxor awnings are built to last.







All operating components are designed and manufactured in Germany and certified by international testing agency TÜV to the European standard 'CE Marking'.

The Secuflex 70II folding arms use tensioned, spring loaded, PVC coated triple steel cables that provide added protection against corrosion. These cables are individually hung to provide excellent wind stability and fabric tension.

The Secuflex 70II arms are able to withstand 120,000 cycles of stress, as certified by Materials Testing Authority of Germany.

Patented pivot ball front bar connector provides the best possible operational safety.

Extruded aluminium profiles for pelmets and cassettes provide solid, stable and long lasting quality that will not rust or vibrate in harsh conditions.

Construction hardware is made of marine grade 316 stainless steel.

Powdercoated galvanised steel support bars have a high durability epoxy undercoat, Pacesetter HP200, 160 microns thick to provide additional anti-corrosion protection.

Patented aluminium brackets and components with pre-treated baked enamel finish.





Oversquare



Starting and start

Celing Installation

Specifications

Dimensions (h x d) Width (single unit) Projection range Standard frame & fascia

Custom frame & fascia Oversquare Vario Volant Fabric Fabric Operating mechanism Automation features

✓: Standard A: Available

- ✓ 210mm x 185mm
- ⁄ 2m 7m
- 1.5m 4m
- ✓ White, silver, cream, black, beige & dark grey powdercoated
- A 140 colours powdercoated
- A Projection greater than width
- A Up to 2m vertical screen
- ✓ Acrylic canvas
- A PVC plastisol coated
- ✓ Manual
- A Motorised, sun, wind & timer systems

Your Authorised Distributor is:



Aluxor Awning Systems Aluxor Industries Pty Ltd www.aluxor.com.au

