

LUXAFLEX®

Awning Canvas

FABRIC COLLECTION



Luxaflex® Awning Canvas Fabric Collection




The Luxaflex® external fabrics canvas range provides the ultimate solution to allowing natural light into the home whilst reducing the level of ambient glare. Our canvas range is proudly made in Australia to withstand even the most demanding Australian conditions and has an extensive array of on-trend modern colour palettes which will continue to look great for years to come.




Yalumba




Custard




Bone



Dream




Grass



Jungle




Silver Pearl




Sky



Coffee



Thundercloud



Urban




Mombasa




Domino



Riveria



Firepit



Tanned



Beach




Chelsea



Henley



Zebra



Hills



Cottage




Turf



Rosie



Sunset



Country

Note: Fabric scan colours are as accurate as the printing process allows.

Luxaflex® Awning Canvas Fabric Collection



FEATURES & BENEFITS

APPLICATIONS

Contemporary Drop Awnings
Pivot Arm Awnings
Timeless Collection Fabric Awnings

COLOUR AND OPACITY

26 External colours

UV RESISTANT

All colours meet Australian Standards for colour fastness to resist fading.

FEATURES

STAIN RESISTANT



Duraguard® Fabric Protector effectively repels most stain causing agents with its proven, water based, preventative formula.

UNTREATED CANVAS

Water easily absorbed into fabric and becomes saturated.



TREATED CANVAS

Water turns to beads, is unable to penetrate into the fabric and will run off leaving it clean and dry.



MADE IN AUSTRALIA

Proudly made in Australia to support the local textile industry.

5 YEAR WARRANTY#

Luxaflex fabrics are backed by a 5 year warranty for your peace of mind.

TECHNICAL SPECIFICATIONS

COMPOSITION

Plain woven, 52% Polyester and 48% Cotton

FABRIC WEIGHT

498gsm ± 10gsm

BREAKING STRENGTH

Warp >2315N, Weft >1700N [Base Cloth]

TEARING RESISTANCE

Warp >50N, Weft >30N [Base Cloth]

COLOUR FASTNESS

6-7 Blue Scale (AS2001.4.21)

ROLL WIDTH

2.2m, 2.8m

CARE & CLEANING

GENERAL CARE

Dusting with a feather duster is all that is required to keep your fabric looking good.

STAINS

For the removal of dirt and grime, simply wipe fabric skins with a sponge soaked in lukewarm water. If marks are still visible add a little detergent. Then dry gently with a clean cloth.

SOLAR OPTICAL GUIDE

COLOUR	HEAT PROPERTIES			VISIBLE LIGHT PROPERTIES
	TS	RS	AS	TL (TV)
C15 ROSIE	0	31	69	0
C9200 COUNTRY	0	39	61	0
C181 URBAN	0	7	93	0

The fenestration property tests were conducted in accordance with EN 410 (1998), EN 14501: (2005) and EN 14500: (2008). Solar radiation is always partially transmitted through, absorbed or reflected by the fabric. The sum of all 3 equals 100.

Ts +Rs+As = 100% of solar energy.

SOLAR OPTICAL PROPERTIES GUIDE

TS	Heat Transmittance (%)	AS	Heat Absorbance (%)
RS	Heat Reflectance (%)	TV/TL	Light Transmittance (%)



FIRE RETARDANCY INFORMATION

SPREAD OF FLAME	(Range 0-10)	8
HEAT EVOLVED	(Range 0-10)	6
SMOKE DEVELOPED	(Range 0-10)	6
IGNITABILITY	(Range 0-20)	6
FLAMMABILITY		88

Conditions apply. Visit luxaflex.com.au for warranty details.

© Registered Trade Marks of Hunter Douglas Limited. © Copyright 2022 Hunter Douglas Limited [ABN 98 009 675 709]. 11/22